


High Voltage MLC Chips

For 600V to 5000V Applications



NEW 630V RANGE

High value, low leakage and small size are difficult parameters to obtain in capacitors for high voltage systems. AVX special high voltage MLC chip capacitors meet these performance characteristics and are designed for applications such as snubbers in high frequency power converters, resonators in SMPS, and high voltage coupling/dc blocking. These high voltage chip designs exhibit low ESRs at high frequencies.

Larger physical sizes than normally encountered chips are used to make high voltage MLC chip products. Special precautions must be taken in applying these chips in surface mount assemblies. The temperature gradient during heating or cooling cycles should not exceed 4°C per second. The preheat temperature must be within 50°C of the peak temperature reached by the ceramic bodies through the soldering process. Chip sizes 1210 and larger should be reflow soldered only. Capacitors may require protective surface coating to prevent external arcing.

For 1825, 2225 and 3640 sizes, AVX offers leaded version in either thru-hole or SMT configurations (for details see section on high voltage leaded MLC chips).

HOW TO ORDER


1808	A	A	271	K	A	1	2	A
AVX Style	Voltage	Temperature Coefficient	Capacitance Code	Capacitance Tolerance	Test Level	Termination*	Packaging	Special Code
0805	600V/630V = C	NPO (COG) = A	(2 significant digits + no. of zeros)	COG: J = ±5%	A = Standard	1 = Pd/Ag	1 or 2 = 7" Reel**	A = Standard
1206	1000V = A	X7R = C	Examples:	K = ±10%		T = Plated	3 or 4 = 13" Reel	
1210	1500V = S		10 pF = 100	M = ±20%		Ni and Sn (RoHS Compliant)		
1808	2000V = G		100 pF = 101	X7R: K = ±10%				
1812	2500V = W		1,000 pF = 102	M = ±20%				
1825	3000V = H		22,000 pF = 223	Z = +80%, -20%				
2220	4000V = J		220,000 pF = 224					
2225	5000V = K		1 μF = 105					
3640								

*Note: Terminations with 5% minimum lead (Pb) is available, see pages 100 and 101 for LD style. Leaded terminations are available, see pages 102-106.

Notes: Capacitors with X7R dielectrics are not intended for applications across AC supply mains or AC line filtering with polarity reversal. Contact plant for recommendations. Contact factory for availability of Termination and Tolerance options for Specific Part Numbers.

** The 3640 Style is not available on 7" Reels.

*** AVX offers nonstandard chip sizes. Contact factory for details.



DIMENSIONS

millimeters (inches)

SIZE	0805	1206	1210*	1808*	1812*	1825*	2220*	2225*	3640*
(L) Length	2.10 ± 0.20 (0.083 ± 0.008)	3.30 ± 0.30 (0.130 ± 0.012)	3.30 ± 0.40 (0.130 ± 0.016)	4.60 ± 0.50 (0.181 ± 0.020)	4.60 ± 0.50 (0.181 ± 0.020)	4.60 ± 0.50 (0.181 ± 0.020)	5.70 ± 0.50 (0.224 ± 0.020)	5.72 ± 0.25 (0.225 ± 0.010)	9.14 ± 0.25 (0.360 ± 0.010)
(W) Width	1.25 ± 0.20 (0.049 ± 0.008)	1.60 ^{+0.30} _{-0.10} (0.063 ^{+0.012} _{-0.004})	2.50 ± 0.30 (0.098 ± 0.012)	2.00 ± 0.20 (0.079 ± 0.008)	3.20 ± 0.30 (0.126 ± 0.012)	6.30 ± 0.40 (0.248 ± 0.016)	5.00 ± 0.40 (0.197 ± 0.016)	6.35 ± 0.25 (0.250 ± 0.010)	10.2 ± 0.25 (0.400 ± 0.010)
(T) Thickness Max.	1.35 (0.053)	1.80 (0.071)	2.80 (0.110)	2.20 (0.087)	2.80 (0.110)	3.40 (0.134)	3.40 (0.134)	2.54 (0.100)	2.54 (0.100)
(t) terminal min. max.	0.50 ± 0.20 (0.020 ± 0.008)	0.60 ± 0.20 (0.024 ± 0.008)	0.75 ± 0.35 (0.030 ± 0.014)	0.75 ± 0.35 (0.030 ± 0.014)	0.75 ± 0.35 (0.030 ± 0.014)	0.75 ± 0.35 (0.030 ± 0.014)	0.85 ± 0.35 (0.033 ± 0.014)	0.85 ± 0.35 (0.033 ± 0.014)	0.76 (0.030) 1.52 (0.060)

*Reflow Soldering Only

High Voltage MLC Chips

For 600V to 5000V Applications

NPO (C0G) Dielectric Performance Characteristics

Capacitance Range	10 pF to 0.100 μF (25°C, 1.0 ±0.2 Vrms at 1kHz, for ≤ 1000 pF use 1 MHz)
Capacitance Tolerances	±5%, ±10%, ±20%
Dissipation Factor	0.1% max. (+25°C, 1.0 ±0.2 Vrms, 1kHz, for ≤ 1000 pF use 1 MHz)
Operating Temperature Range	-55°C to +125°C
Temperature Characteristic	0 ±30 ppm/°C (0VDC)
Voltage Ratings	600, 630, 1000, 1500, 2000, 2500, 3000, 4000 & 5000 VDC (+125°C)
Insulation Resistance (+25°C, at 500 VDC)	100K MΩ min. or 1000 MΩ - μF min., whichever is less
Insulation Resistance (+125°C, at 500 VDC)	10K MΩ min. or 100 MΩ - μF min., whichever is less
Dielectric Strength	Minimum 120% rated voltage for 5 seconds at 50 mA max. current

NPO (C0G) CAPACITANCE RANGE – PREFERRED SIZES ARE SHADED

Case Size	0805			1206					1210					1808							1812										
	Reflow/Wave			Reflow/Wave					Reflow Only					Reflow Only							Reflow Only										
(L) Length	2.10 ±0.20 (0.085 ±0.008)			3.30 ±0.30 (0.130 ±0.012)					3.30 ±0.40 (0.130 ±0.016)					4.80 ±0.50 (0.181 ±0.020)							4.80 ±0.50 (0.177 ±0.012)										
(W) Width	1.25 ±0.20 (0.049 ±0.008)			1.60 ±0.30/-0.10 (0.063 ±0.012/-0.004)					2.50 ±0.30 (0.098 ±0.012)					2.00 ±0.20 (0.079 ±0.008)							3.20 ±0.30 (0.126 ±0.008)										
(T) Thickness	1.35 (0.053)			1.80 (0.071)					2.80 (0.110)					2.20 (0.087)							2.80 (0.100)										
(t) Terminal	0.50 ±0.20 (0.020 ±0.008)			0.60 ±0.20 (0.024 ±0.008)					0.75 ±0.35 (0.030 ±0.014)					0.75 ±0.35 (0.030 ±0.014)							0.75 ±0.35 (0.030 ±0.014)										
Voltage (V)	600	630	1000	600	630	1000	1500	2000	600	630	1000	1500	2000	3000	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000	
5 0R5																															
1.0 1R0																															
1.2 1R2																															
1.5 1R5	A	A	C	X	X	X	X	X																							
1.8 1R8	A	A	C	X	X	X	X	X																							
2.2 2R2	A	A	C	X	X	X	X	X																							
2.7 2R7	A	A	C	X	X	X	X	X																							
3.3 3R3	A	A	C	X	X	X	X	X																							
3.9 3R9	A	A	C	X	X	X	X	X																							
4.7 4R7	A	A	C	X	X	X	X	X																							
5.6 5R6	A	A	C	X	X	X	X	X																							
6.8 6R8	A	A	C	X	X	X	X	X																							
8.2 8R2	A	A	C	X	X	X	X	X																							
10 100	A	A	C	X	X	X	X	X																							
12 120	A	A	C	X	X	X	X	X																							
15 150	A	A	C	X	X	X	X	X																							
18 180	A	A	C	X	X	X	X	X																							
22 220	A	A	C	X	X	X	X	X																							
27 270	A	A	C	X	X	X	X	X																							
33 330	A	A	C	X	X	X	X	D	M	C	M	M	D	M	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
39 390	A	A	C	X	X	X	X	D	M	C	M	M	D	M	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
47 470	A	A	C	X	X	X	M	D	M	C	M	M	D	M	F	F	F	F	F	F	F	F	F	F	F	F	F	F	F		
56 560	A	A	C	X	X	X	M	D	C	C	M	M	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C		
68 680	A	A	C	X	X	X	M	C	C	C	M	M	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C		
82 820	X	X	X	X	X	X	C	C	C	C	C	M	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C		
100 101	X	X	X	X	X	X	C	C	C	C	C	M	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C		
120 121	C	C	C	X	X	X	C	E	E	E	E	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C		
150 151	C	C	C	X	X	X	C	E	E	E	E	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C		
180 181	C	C	C	X	X	X	E	E	E	E	E	M	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C		
220 221	C	C	C	X	X	X	E	E	E	E	E	M	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C		
270 271	C	C	C	C	C	M	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
330 331	C	C	C	C	C	M	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
390 391	C	C	C	C	C	M	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
470 471	C	C	C	C	C	M	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
560 561	C	C	C	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
680 681	C	C	C	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
750 751	C	C	C	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
820 821	C	C	C	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
1000 102	C	C	C	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
1200 122	C	C	C	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
1500 152	C	C	C	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
1800 182	C	C	C	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
2200 222	C	C	C	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
2700 272	C	C	C	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
3300 332							E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
3900 392							E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
4700 472							E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
5600 562							E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
6800 682							E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
8200 822							E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E		
Cap (pF) 0.010 103																															
0.012 123																															
0.015 153																															
0.018 183																															
0.022 223																															
0.027 273																															
0.033 333																															
0.047 473																															
0.056 563																															
0.068 683																															
0.100 104																															
0.12 124																															
0.15 154																															
0.18 184																															
0.22 224																															
0.27 274																															
0.33 334																															
Voltage (V)	600	630	1000	600	630	1000	1500	2000	600	630	1000	1500	2000	3000	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000	
Case Size	0805			1206					1210					1808							1812										

Letter	A	C	E	F	G	X	7
--------	---	---	---	---	---	---	---

High Voltage MLC Chips

For 600V to 5000V Applications

NPO (C0G) CAPACITANCE RANGE – PREFERRED SIZES ARE SHADED

Case Size	1825								2220								2225								3640											
Soldering	Reflow Only								Reflow Only								Reflow Only								Reflow Only											
(L) Length mm	4.60 ±0.50								5.70 ±0.50								5.70 ±0.50								9.14 ±0.25											
(L) Length (in.)	(0.181 ±0.020)								(0.224 ±0.020)								(0.225 ±0.010)								(0.360 ±0.010)											
(W) Width mm	6.30 ±0.40								5.00 ±0.40								6.30 ±0.40								10.2 ±0.25											
(W) Width (in.)	(0.248 ±0.016)								(0.197 ±0.016)								(0.250 ±0.010)								(0.400 ±0.010)											
(T) Thickness mm	3.40								3.40								3.40								2.54											
(T) Thickness (in.)	(0.134)								(0.134)								(0.100)								(0.100)											
(t) Terminal min	0.75 ±0.35								0.85 ±0.35								0.85 ±0.35								0.76 (0.050)											
(t) Terminal max	(0.030 ±0.014)								(0.033 ±0.014)								(0.033 ±0.014)								1.52 (0.060)											
Voltage (V)	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000	
Cap (pF)	1.5 1R5								1.5 1R5									1.5 1R5									1.5 1R5									
Cap (pF)	1.8 1R8								1.8 1R8									1.8 1R8									1.8 1R8									
Cap (pF)	2.2 2R2								2.2 2R2									2.2 2R2									2.2 2R2									
Cap (pF)	2.7 2R7								2.7 2R7									2.7 2R7									2.7 2R7									
Cap (pF)	3.3 3R3								3.3 3R3									3.3 3R3									3.3 3R3									
Cap (pF)	3.9 3R9								3.9 3R9									3.9 3R9									3.9 3R9									
Cap (pF)	4.7 4R7								4.7 4R7									4.7 4R7									4.7 4R7									
Cap (pF)	5.6 5R6								5.6 5R6									5.6 5R6									5.6 5R6									
Cap (pF)	6.8 6R8								6.8 6R8									6.8 6R8									6.8 6R8									
Cap (pF)	8.2 8R2								8.2 8R2									8.2 8R2									8.2 8R2									
Cap (pF)	10 100	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	12 120	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	15 150	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	18 180	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	22 220	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	27 270	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	33 330	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	39 390	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	47 470	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	56 560	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	68 680	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	82 820	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	100 101	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	120 121	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	150 151	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	180 181	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	220 221	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	270 271	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	330 331	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	390 391	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	470 471	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	560 561	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	680 681	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	750 751	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	820 821	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	1000 102	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	1200 122	E	E	G	E	F	E	F	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E		
Cap (pF)	1500 152	E	E	G	F	G	G	G	E	E	E	F	F	G	G	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E			
Cap (pF)	1800 182	E	E	G	F	G	G	G	E	E	E	F	F	G	G	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E			
Cap (pF)	2200 222	E	E	G	F	G	G	G	E	E	E	F	F	G	G	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E			
Cap (pF)	2700 272	E	E	G	F	G	G	G	E	E	E	F	F	G	G	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E			
Cap (pF)	3300 332	E	E	G	F	G	G	G	E	E	E	F	F	G	G	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E			
Cap (pF)	3900 392	E	E	G	F	G	G	G	E	E	E	F	F	G	G	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E			
Cap (pF)	4700 472	E	E	G	F	G	G	G	E	E	E	F	F	G	G	E	E	E	E	E	E	E	E	F	F	E	E	E	E	E	E	E	E			
Cap (pF)	5600 562	F	F	G	G	G	G	F	F	F	G	G	G	F	F	F	G	G	F	F	F	G	G	G	F	F	F	G	G	G	F	F	F	G	G	G
Cap (pF)	6800 682	F	F	G	G	G	G	F	F	F	G	G	G	F	F	F	G	G	F	F	F	G	G	G	F	F	F	G	G	G	F	F	F	G	G	G
Cap (pF)	8200 822	F	F	G	G	G	G	F	F	F	G	G	G	F	F	F	G	G	F	F	F	G	G	G	F	F	F	G	G	G	F	F	F	G	G	G
Cap (pF)	0.010 103	F	F	G	G	G	G	F	F	F	G	G	G	F	F	F	G	G	F	F	F	G	G	G	F	F	F	G	G	G	F	F	F	G	G	G
Cap (pF)	0.012 123	F	F	G	G	G	G	F	F	F	G	G	G	F	F	F	G	G	F	F	F	G	G	G	F	F	F	G	G	G	F	F	F	G	G	G
Cap (pF)	0.015 153	F	F	G	G	G	G	F	F	F	G	G	G	F	F	F	G	G	F	F	F	G	G	G	F	F	F	G	G	G	F	F	F	G	G	G
Cap (pF)	0.018 183	F	F	G	G	G	G	F	F	F	G	G	G	F	F	F	G	G	F	F	F	G	G	G	F	F	F	G	G	G	F	F	F	G	G	G
Cap (pF)	0.022 223	F	F	G	G	G	G	F	F	F	G	G	G	F	F	F	G	G	F	F	F	G	G	G	F	F	F	G	G	G	F	F	F	G	G	G
Cap (pF)	0.027 227	F	F	G	G	G	G	F	F	F	G	G	G	F	F	F	G	G	F	F	F	G	G	G	F	F	F	G	G	G	F	F	F	G	G	G
Cap (pF)	0.033 333	F	F	G	G	G	G	F	F	F	G	G	G	F	F	F	G	G	F	F	F	G	G	G	F	F	F	G	G	G	F	F	F	G	G	G
Cap (pF)	0.039 393	G	G					G	G					G	G				G	G					G	G					G	G				
Cap (pF)	0.047 473	G	G					G	G					G	G																					

High Voltage MLC Chips

For 600V to 5000V Applications

X7R Dielectric Performance Characteristics

Capacitance Range	10 pF to 0.82 μF (25°C, 1.0 ±0.2 Vrms at 1kHz)
Capacitance Tolerances	±10%; ±20%; +80%, -20%
Dissipation Factor	2.5% max. (+25°C, 1.0 ±0.2 Vrms, 1kHz)
Operating Temperature Range	-55°C to +125°C
Temperature Characteristic	±15% (0VDC)
Voltage Ratings	600, 630, 1000, 1500, 2000, 2500, 3000, 4000 & 5000 VDC (+125°C)
Insulation Resistance (+25°C, at 500VDC)	100K MΩ min. or 1000 MΩ - μF min., whichever is less
Insulation Resistance (+125°C, at 500VDC)	10K MΩ min. or 100 MΩ - μF min., whichever is less
Dielectric Strength	Minimum 120% rated voltage for 5 seconds at 50 mA max. current

X7R CAPACITANCE RANGE – PREFERRED SIZES ARE SHADED

Case Size	0805			1206				1210				1808				1812													
	Reflow/Wave			Reflow/Wave				Reflow Only				Reflow Only				Reflow Only													
(L) Length mm	2.10 ±0.20 (0.085 ±0.008)			3.30 ±0.30 (0.130 ±0.012)				3.30 ±0.40 (0.130 ±0.016)				4.60 ±0.50 (0.181 ±0.020)				4.60 ±0.50 (0.177 ±0.012)													
(W) Width mm	1.25 ±0.20 (0.049 ±0.008)			1.60 ±0.30/-0.10 (0.063 ±0.012/-0.004)				2.50 ±0.30 (0.098 ±0.012)				2.00 ±0.20 (0.079 ±0.008)				3.20 ±0.30 (0.126 ±0.008)													
(T) Thickness mm	1.35 (0.053)			1.80 (0.071)				2.80 (0.110)				2.20 (0.087)				2.80 (0.100)													
(t) Terminal min max	0.50 ±0.20 (0.020 ±0.008)			0.60 ±0.20 (0.024 ±0.008)				0.75 ±0.35 (0.030 ±0.014)				0.75 ±0.35 (0.030 ±0.014)				0.75 ±0.35 (0.030 ±0.014)													
Voltage(V)	600	630	1000	600	630	1000	1500	2000	600	630	1000	1500	2000	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000
Cap (pF)	100	101	X	X	C	C	C	E	E	E	E	E	E																
	120	121	X	X	C	C	C	E	E	E	E	E	E																
	150	151	X	X	C	C	C	E	E	E	E	E	E																
	180	181	X	X	C	C	C	E	E	E	E	E	E																
	220	221	X	X	C	C	C	E	E	E	E	E	E																
	270	271	X	X	C	C	C	E	E	E	E	E	E										E	E	E	E	E	E	
	330	331	X	X	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	F		E	E	E	E	E	E	
	390	391	X	X	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	E	F		E	E	E	E	E	E	
	470	471	X	X	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	F	F		E	E	E	E	E	E	E
	560	561	X	X	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	F	F		E	E	E	E	E	E	E
	680	681	X	X	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	F	F		E	E	E	E	E	F	F
	750	751	X	X	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	F	F		E	E	E	E	E	F	F
	820	821	X	X	C	C	C	E	E	E	E	E	E	E	E	E	E	E	E	F	F		E	E	E	E	E	F	F
	1000	102	X	X	X	C	C	E	E	E	E	E	E	E	E	E	E	E	E	F	F		E	E	E	E	E	F	F
	1200	122	X	X	X	C	C	E	E	E	E	E	E	E	E	E	E	E	E	F	F		E	E	E	E	E	F	F
	1500	152	X	X	X	C	C	E	E	E	E	E	E	E	E	E	E	E	E	F	F		E	E	E	E	E	F	F
	1800	182	X	X	X	C	C	E	E	E	E	E	E	E	E	E	E	E	E	F	F		E	E	E	E	E	F	F
	2200	222	X	X	X	C	C	E	E	E	E	E	E	E	E	E	E	E	E	F	F		E	E	E	E	E	F	F
	2700	272	C	C		C	C	E	E						E	E	E	F	F				E	E	E	E	E	G	G
	3300	332	C	C		C	C	E	E						E	E	E	F	F				E	E	E	F	F	G	G
	3900	392	C	C		C	C	E	E						E	E	E	F	F				E	E	E	F	F	G	G
	4700	472	C	C		C	C	E	E						E	E	E	F	F				E	E	E	F	F	G	G
	5600	562	C	C		C	C	E	E						E	E	E	F	F				E	E	E	G	G	G	G
	6800	682	C	C		C	C	E	E						E	E	E	F	F				E	E	E	G	G	G	G
	8200	822	C	C		C	C	E	E						E	E	E	F	F				E	E	E	G	G	G	G
Cap (μF)	0.010	103	C	C		C	C	E	E						E	E	E	F	F				E	E	F	G	G	G	G
	0.015	153	C	C		E	E	E							E	E	E	F	F	F			E	E	F	G			
	0.018	183	C	C		E	E	E							E	E	E	F	F	F			E	E	G				
	0.022	223	C	C		E	E	E							E	E	E	F	F	F			E	E	G		G		
	0.027	273				E	E	E							E	E	E	F	F	F			E	E	G				
	0.033	333				E	E								E	E	E	G					E	E	G				
	0.039	393				E	E	F							E	E	F						E	E	G				
	0.047	473				E	E								E	E	F						E	E	G				
	0.056	563													F	F							F	F					
	0.068	683													F	F							F	F					
	0.082	823													F	F							F	F					
	0.100	104													F	F							F	F					
	0.150	154																						G	G				
	0.220	224																						G	G				
	0.270	274																						G	G				
	0.330	334																						G	G				
	0.390	394																											
	0.470	474																											
	0.560	564																											
	0.680	684																											
	0.820	824																											
	1.000	105																											
Voltage(V)	600	630	1000	600	630	1000	1500	2000	600	630	1000	1500	2000	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000
Case Size	0805			1206				1210				1808				1812													

Letter	A	C	E	F	G	X	7
Max. Thickness	0.813 (0.032)	1.448 (0.057)	1.8034 (0.071)	2.2098 (0.087)	2.794 (0.110)	0.940 (0.037)	3.30 (0.130)

NOTE: Contact factory for non-specified capacitance values

High Voltage MLC Chips

For 600V to 5000V Applications

X7R CAPACITANCE RANGE
PREFERRED SIZES ARE SHADED

Case Size	1825								2220								2225								3640										
Soldering	Reflow Only								Reflow Only								Reflow Only								Reflow Only										
(L) Length mm (in.)	4.60 ±0.50 (0.181 ±0.020)								5.70 ±0.50 (0.224 ±0.020)								5.70 ±0.50 (0.225 ±0.010)								9.14 ±0.25 (0.360 ±0.010)										
(W) Width mm (in.)	6.30 ±0.40 (0.248 ±0.016)								5.00 ±0.40 (0.197 ±0.016)								6.30 ±0.40 (0.250 ±0.010)								10.2 ±0.25 (0.400 ±0.010)										
(T) Thickness mm (in.)	3.40 (0.134)								3.40 (0.134)								3.40 (0.100)								2.54 (0.100)										
(t) Terminal min max	0.75 ±0.35 (0.030 ±0.014)								0.85 ±0.35 (0.033 ±0.014)								0.85 ±0.35 (0.033 ±0.014)								0.76 (0.030) 1.52 (0.060)										
Voltage (V)	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000
Cap (pF)	100	101							100	101								100	101								100	101							
Cap (pF)	120	121							120	121							120	121								120	121								
Cap (pF)	150	151							150	151							150	151								150	151								
Cap (pF)	180	181							180	181							180	181								180	181								
Cap (pF)	220	221							220	221							220	221								220	221								
Cap (pF)	270	271							270	271							270	271								270	271								
Cap (pF)	330	331							330	331							330	331								330	331								
Cap (pF)	390	391							390	391							390	391								390	391								
Cap (pF)	470	471							470	471							470	471								470	471								
Cap (pF)	560	561							560	561							560	561								560	561								
Cap (pF)	680	681							680	681							680	681								680	681								
Cap (pF)	750	751							750	751							750	751								750	751								
Cap (pF)	820	821							820	821							820	821								820	821								
Cap (pF)	1000	102	F	F	F	F	F	F	F	F	F	F	F	F	F	G	F	F	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G		
Cap (pF)	1200	122	F	F	F	F	F	F	F	F	F	F	F	F	F	G	F	F	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G		
Cap (pF)	1500	152	F	F	F	F	F	F	F	F	F	F	F	F	F	G	F	F	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G		
Cap (pF)	1800	182	F	F	F	F	F	F	F	F	F	F	F	F	F	G	F	F	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G		
Cap (pF)	2200	222	F	F	F	F	F	F	F	F	F	F	F	F	F	G	F	F	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G		
Cap (pF)	2700	272	F	F	F	F	F	F	F	F	F	F	F	F	F	G	F	F	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G		
Cap (pF)	3300	332	F	F	F	F	F	F	F	F	F	F	F	F	F	G	F	F	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G		
Cap (pF)	3900	392	F	F	F	F	F	F	F	F	F	F	F	F	F	G	F	F	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G		
Cap (pF)	4700	472	F	F	F	F	F	F	F	F	F	F	F	F	F	G	F	F	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G		
Cap (pF)	5600	562	F	F	F	F	F	F	F	F	F	F	F	F	F	G	F	F	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G		
Cap (pF)	6800	682	F	F	F	G	G	G	F	F	F	F	F	F	G	G	F	F	F	F	F	F	G	G	G	G	G	G	G	G	G	G	G		
Cap (pF)	8200	822	F	F	F	G	G	G	F	F	F	G	G	G	G	F	F	F	F	F	G	G	G	G	G	G	G	G	G	G	G	G			
Cap (µF) 0.010	103	F	F	F	G	G	G	G	F	F	F	G	G	G	G	F	F	F	F	F	G	G	G	G	G	G	G	G	G	G	G	G			
Cap (µF)	0.015	153	F	F	F	G	G	G	F	F	F	G	G	G	G	F	F	F	G	G	G	G	G	G	G	G	G	G	G	G	G	G			
Cap (µF)	0.018	183	F	F	F	G	G	G	F	F	F	G	G	G	G	F	F	F	G	G	G	G	G	G	G	G	G	G	G	G	G	G			
Cap (µF)	0.022	223	F	F	F	G	G	G	F	F	F	G	G	G	G	F	F	F	G	G	G	G	G	G	G	G	G	G	G	G	G	G			
Cap (µF)	0.027	273	F	F	F	G	G	G	F	F	F	G	G	G	G	F	F	F	G	G	G	G	G	G	G	G	G	G	G	G	G	G			
Cap (µF)	0.033	333	F	F	F	G	G	G	F	F	F	G	G	G	G	F	F	F	G	G	G	G	G	G	G	G	G	G	G	G	G	G			
Cap (µF)	0.039	393	F	F	F	G	G	G	F	F	F	G	G	G	G	F	F	F	G	G	G	G	G	G	G	G	G	G	G	G	G	G			
Cap (µF)	0.047	473	F	F	F	P			F	F	F	G				F	F	F	G					G	G	G	G								
Cap (µF)	0.056	563	F	F	F	G			F	F	F	G				F	F	F	G					G	G	G	G								
Cap (µF)	0.068	683	F	F	G				F	F	G					F	F	F	G					G	G	G	G								
Cap (µF)	0.082	823	F	F	G				F	F	G					F	F	G						G	G	G	G								
Cap (µF)	0.100	104	F	F	G				F	F	G					F	F	G						G	G	G	G								
Cap (µF)	0.150	154	F	F					F	F	G					F	F	G						G	G	G	G								
Cap (µF)	0.220	224	F	F					F	F	G					F	F	G						G	G	G									
Cap (µF)	0.270	274	F	F					F	F						F	F							G	G										
Cap (µF)	0.330	334	F	F					F	F						F	F							G	G										
Cap (µF)	0.390	394	F	F					F	F						F	F							G	G										
Cap (µF)	0.470	474	F	F					F	F						F	F							G	G										
Cap (µF)	0.560	564	G	G					G	G						F	F							G	G										
Cap (µF)	0.680	684							G	G						G	G																		
Cap (µF)	0.820	824							G	G						G	G																		
Cap (µF)	1.000	105							G	G						G	G																		
Voltage (V)	600	630	1000	1500	2000	2500	3000	4000	600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000	600	630	1000	1500	2000	2500	3000	4000	5000
Case Size	1825								2220								2225								3640										

Letter	A	C	E	F	G	X	7
Max. Thickness	0.813 (0.032)	1.448 (0.057)	1.8034 (0.071)	2.2098 (0.087)	2.794 (0.110)	0.940 (0.037)	3.30 (0.130)

NOTE: Contact factory for non-specified capacitance values

