

# RoHS Compliant Mini-TurboCap™

## Small Footprint, High Volumetric Efficiency, High-CV SMPS Capacitors



The RoHS Compliant Mini-TurboCap™ is constructed from state-of-the-art BME (Base Metal Electrode) MLC Capacitors achieving very high CV, as well as, ultra low ESR and ESL. The resulting, very large capacitance values allow for component and board space reduction. Stress relieving lead frames provide effective mechanical decoupling of the ceramic chips from the board, minimizing the stress created by board flexing, vibration and temperature cycling. High temperature solder is used to attach chips to the lead frame thus eliminating the risk of solder reflow during assembly to the board.

### CAPACITANCE RANGE

Cap (µF)	Voltage		
	25V	50V	100V
8.2			
18			
39*			
82*			



### HOW TO ORDER

RT10	5	C	186	M	A	K	02
<b>AVX Style</b>	<b>Voltage</b> 25V = 3 50V = 5 100V = 1	<b>Temperature Coefficient</b> X7R = C	<b>Capacitance Code</b> (2 significant digits + no. of zeros) 1 µF = 105 10 µF = 106	<b>Capacitance Tolerance</b> M = ±20%	<b>Test Level</b> A = Standard	<b>Termination</b> N = Straight Lead K = Leads formed in M = Leads formed out	<b>Number of Leads Per Side</b> 02 = 2

Additional stacked/lead configurations available upon request. Consult with AVX factory personnel for details.

### ELECTRICAL SPECIFICATIONS

#### Temperature Coefficient

±15%, -55° to +125°C

#### Capacitance Test (MIL-STD-202, Method 305)

25°C, 1.0±0.2 Vrms (open circuit voltage) at 1KHz

#### Dissipation Factor

5% Max @ 25°C, for 50VDC and 100VDC voltage ratings

#### Insulation Resistance 25°C (MIL-STD-202, Method 302)

500 MΩ-µF (\*100 MΩ-µF)

#### Insulation Resistance 125°C (MIL-STD-202, Method 302)

50 MΩ-µF (\*10 MΩ-µF)

#### Dielectric Withstanding Voltage 25°C (Flash Test)

250% rated voltage for 5 seconds with 50 mA max charging current.

#### Life Test Capabilities (1000 hrs)


150% rated voltage at +125°C.




# RoHS Compliant Mini-TurboCap™

Small Footprint, High Volumetric Efficiency,  
High-CV SMPS Capacitors


## STYLE/DIMENSIONS



**"N" STYLE LEADS**



**"K" STYLE LEADS**



**"M" STYLE LEADS**

## DIMENSIONS

millimeters (inches)

Style	A (max.)	B (max.)	C ± 0.635 (± 0.025)	D ± 0.635 (± 0.025)	E (max.)	No. of Leads Per Side
RT10	5.59 (0.220)	7.00 (0.275)	3.81 (0.150)	5.33 (0.210)	4.83 (0.190)	02

## PART NUMBER AVAILABLE OPTIONS (2X2)

Part Number	Temperature Coefficient	Voltage	Capacitance Code	Capacitance	Capacitance Tolerance	Number Of Leads	Lead Styles
RT103C826MA-02	X7R	25	826	82µF	±20%	2	N, K, M
RT105C186MA-02	X7R	50	186	18µF	±20%	2	N, K, M
RT105C396MA-02	X7R	50	396	39µF	±20%	2	N, K, M
RT101C825MA-02	X7R	100	825	8.2µF	±20%	2	N, K, M